



RUV1804

RUV2004

Ricoh Gen5/6 Printer(4heads)



<p>W W 720*900 6Pass 13m²/h CMYK 720*1200 8Pass 10m²/h</p>	<p>CMYK 720*900 6Pass 26m²/h CMYK 720*1200 8Pass 20m²/h</p>	<p>WCV 720*900 6Pass 6.5m²/h 720*1200 8Pass 5m²/h</p>	<p>CWC 720*900 6Pass 4.3m²/h 720*1200 8Pass 3.3m²/h</p>



1
 Carriage Position System : 180DPI Grating Positioning System
 Carriage Lifting System : Manual Screw type Carriage Lifting System
 Printhead Protection System : Carriage Anti Collision System
 Anti static electric system (Optional): Carriage Anti-static Device,



2
 Main Girder Structure: 200*100*4MM Square Tube
 Carriage Beam: 2955mm thickened Aluminum Beam
 Linear Guide Way(Optional): Two THK linear guide way With Four Blocks
 Pinch Roller: 24PCS High Precision Aluminum Made Pinch Roller




3
 Printing Bed(optional): 195mm Wide Printing Bed
 Material Suction System: Adjustable Vacuum Suction System
 LED lighting System: Printing Bed Lighting System
 Y Driving Mode: 20mm Diameter Steel Axis



4
 Image Drying System: LED UV Curing With Air Cooling System
 Printhead Cleaning System: Individual Ink Purging System
 Subtank Heater: Subtank Heater



5
 Roll Material Feeding System: Step-Free Feeding System
 Vinyl Feeding System: Double roll Vinyl feeding system
 Big Roll Material Holding System(Optional): Big Roll Material Holding System
 Ink Refilling bottle with sensor: Ink Refilling bottle with sensor



6
 Carriage Capping System: Unique Printhead Protection Stack



7
 Computer Monitor(Optional): Acer 18.5 Inch LCD screen
 LCD&Key board Bracket(Optional): Aluminum LCD &Key board bracket

Maximum print width	1.8M
Number of printhead	4
Printing color	CMYK 4color/CMYK Lm Lc 6color
Compatible ink	UV ink
Special	Wallpaper/Canvas/Chinese art paper/Mesh
Medium transmission	Auto media take-up system
Operation system	Win7、Win10
RIP Software	PhotoPrint
Interface	Reticle
Power requirements	AC220V 50/60HZ 1800W
Working environment	Temperature: 15-30°C Relative Humidity: 40-65%

Packing Details

Printer Size:(L*W*H)	3400*1250*1600MM		
Intergrated packing size	3600*1150*1700MM		
Split packingsize	4200*750*1130MM		
N.W.	520KG	G.W.	650KG
20GP Container	20GP can load 6 pcs	40HQ	40HQ can load 12 pcs

E-110, Sumel-7,Nr. Soni Ni Chali Cross Road,Odhav Road, Ahmedabad, Gujarat.

Mo: 9925007279 / 7600806349 E-mail : khodiyar.enterprise@hotmail.com